

ALCATEL-LUCENT 8232 DECT HANDSET

The Alcatel-Lucent 8232 DECT Handset offers easy-to-use, cost-effective and reliable voice communication, addressing mobility needs in evolving business environments. The 8232 DECT Handset provides a convenient and practical solution for the basic personal mobility needs of most business environments. It offers simple and efficient voice communication, enhanced usability and compatibility with existing Alcatel-Lucent DECT base stations. The 8232 DECT Handset also provides all of the Alcatel-Lucent communication servers value-added voice services (such as dial-by-name and multiline management) that Alcatel-Lucent fixed desk phones support.



FEATURES

- Alcatel-Lucent telephony protocol (AGAP)
- Lightweight, ergonomic design and intuitive operation
- Color display 1.4" 65k colors TFT 128x128 pixels
- Keypad and display backlight
- Handsfree, microphone mute and vibrate modes
- Headset jack (3.5 mm)
- Antenna diversity
- Direct micro USB charging
- Spring loaded belt clip

BENEFITS

- Compatibility with deployed Alcatel-Lucent base stations provides infrastructure investment protection
- Supports large OXE campus configurations
- IP-DECT connectivity
- Excellent voice quality and business telephony features improve user responsiveness and business productivity
- Simplifies business inventory by offering a single product, operational worldwide
- Green: Economy mode uses automatic low radio emission power (25 mW peak)
- Low power mode (50 mW) makes it suitable for demanding environments
- Provides reliability with long battery life

TECHNICAL SPECIFICATIONS

Detailed features

- System languages: Communication server-dependent
- Handset MMI languages (GAP mode and system-independent features)
 - English
 - French
 - German
 - Spanish
 - Italian
 - Dutch
 - Portuguese
 - Danish
 - Swedish
 - Norwegian
 - Finnish
- Handsfree, microphone mute and vibrate modes
- LED for status indication; three colors (green/orange/red) for battery status, missed calls and messages
- Ring tones
 - Six user-selectable polyphonic tones
 - Volume control: four settings; meeting mode
- Supports all AGAP features on Alcatel-Lucent communication servers with TDM infrastructure
- Supports all AGAP features on OmniPCX® Enterprise Communication Server with IP-DECT infrastructure
- Supports GAP features on OXO Connect and OmniPCX Office RCE communication servers
- Call by name: Personal and system directory
- Call log (GAP mode):
 - All, answered, dialed, missed
 - Up to 50 call logs
- Contacts (GAP mode)
 - Name, up to 4 numbers per contact
 - Up to 50 contacts
 - 8 speed-dial options
- Audio and LED message signaling

Radio specifications

- DECT
- Frequency band
 - DECT Europe: 1880 MHz – 1900 MHz
 - DECT 6.0 North America: 1920 MHz – 1930 MHz
 - DECT Latin America: 1910 MHz – 1930 MHz except Brazil 1910-1920 Mhz
 - DECT Asia: 1900 MHz – 1906 MHz
- Handover: Bearer, connection, external
- Out-of-coverage signaling
- Antenna diversity
- Automatic band switching for cruise ship applications (requires IP-DECT)

Wireless security

- Identity
- Authentication
- Encryption

Registration

- Up to four systems
- Manual selection
- Automatic selection

Audio CODECs

- G726

Physical characteristics

- Box contains handset, battery, belt clip and regulatory notice
- Color: Black
- Graphic display: 1.4 in.; 65,000 colors; 128 x 128 pixels
- Display backlight: White
- Keypad backlight: Blue
- Belt clip: Spring loaded; optional swivel clip
- Headset: Jack 3.5 mm; TRRS compliant

Dimensions

- Height: 5.19 in. (133 mm)
- Width: 2.00 in. (52 mm)
- Depth: 0.90 in. (23 mm)

Mechanical characteristics

- Charging on desktop charger or Micro USB-type B plug

Battery pack

- Easily replaceable, 1,100-mAh lithium-ion battery
- Talk time: Up to 20 hours
- Standby time: Up to 200 hours
- Charging time: Less than 3 hours

Operating environment

- Operating temperature: 14°F to 113°F (-10°C to +45°C)
- Storage temperature: -13°F to +131°F (-25°C to +55°C)

Serviceability

- Site survey tool
- Diagnostic mode
- Syslog mode
- Software update over the air (SUOTA) ready – requires IP-DECT

Software management tools

- Download tool (see Accessories)
- Flash loader PC application

Regulatory

EU directives

- R&TTE 1999/5/EC
- LVD2006/95/EC
- EMC 2004/108/EC
- Eco design 2006/32/EC

Safety

- IEC 60950-1
- CAN/CSA-22.2 No 60950-1

EMC and radio

- EN 301 489-1
- EN 301 489-6
- IEC/EN 61000-4-2 Level 3 criteria B
- IEC/EN 61000-4-3 Level 3 criteria A
- EN 301 406 (TBR6)
- FCC 47CFR part 15 subpart D
- IC RSS-213

SAR

- EN 50360
- IEC 62209
- FCC OET Bulletin 65
- IEE 1528
- SAR value: 0.102 W/kg

Audio, hearing aid

- FCC 47CFR Part 68
- Canada: CS-03 part V
- ANSI/TIA/EIA-504-A
- Australia: ACIF S040

Telecom

- EN 301 406 (TBR6)
- EN 300 176-2 (TBR10)
- EN 300 175-8 (DECT audio)
- TBR22
 - ETSI TS 102 841 (security)
 - ES 202 738 (group listening)
- DECT security certification program stepA
- DECT security certification program stepB

Local regulations

- Australia: ACIF S004
- US/Canada: FCC part 68
- New Zealand: PTC220

Acoustic shocks

- UL 1950
- ETS 300 245-2

Environmental

- Operation: ETS 300 019 part 1-7 class 7.2
- Storage: ETS 300 019 part 1-1 class 1.2
- Transport: ETS 300 019 -part 1-2 class 2.3
- IP Class: EN 60529 IP40

Accessories

- 3BN67331AA desktop charger: Charges one handset (with USB cable)
- 3BN67335AA power supply for European plugs
- 3BN67336AA power supply for US, UK and Australian plugs
- 3BN67332AA spare battery
- 3BN67333AA spare belt clip
- 3BN67334AA swivel clip
- 3BN67337AA vertical pouch
- 3BN67338AA horizontal pouch
- 3BN67339AA download tool

enterprise.alcatel-lucent.com

Alcatel-Lucent and the Alcatel-Lucent Enterprise logo are trademarks of Alcatel-Lucent. To view other trademarks used by affiliated companies of ALE Holding, visit: enterprise.alcatel-lucent.com/trademarks. All other trademarks are the property of their respective owners. The information presented is subject to change without notice. Neither ALE Holding nor any of its affiliates assumes any responsibility for inaccuracies contained herein. (September 2016)